(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 29 September 2005 (29.09.2005)

(10) International Publication Number WO 2005/091130 A3

(51) International Patent Classification: *G06F 9/38* (2006.01)

(21) International Application Number:

PCT/IB2005/050684

(22) International Filing Date:

24 February 2005 (24.02.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(**30**) **Priority Data:** 04100975.4

10 March 2004 (10.03.2004) EP

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BINK, Adrianus, J. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). DE CLERCQ, Mark, N., O. [BE/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agents: ELEVELD, Koop, J. et al.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

 as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))


Published:

with international search report

(88) Date of publication of the international search report: 27 July 2006

[Continued on next page]

(54) Title: INSTRUCTION PIPELINE



(57) Abstract: There is provided an electronic circuit adapted to process a plurality of types of instruction, the electronic circuit comprising first and second pipeline stages and a latch positioned between the pipeline stages; wherein the electronic circuit is adapted to operate in a normal mode when processing a first type of instruction in which the latch is opened and closed in response to an enable signal, and a reduced mode when processing a second type of instruction in which the latch is held open so that the instruction propagates through the first and second pipeline stages without being stored in the latch; and wherein the first type of instruction requires processing by the second pipeline stages.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.